

# BALITHERM IONIT ST wear-resistant and non-magnetic

For the treatment of austenitic and non-corrosive martensitic steels



# **BALITHERM IONIT ST – a reliable diffusion process** for austenites and non-corrosive martensites

With the new BALITHERM® IONIT ST process, Oerlikon Balzers has developed a reliable diffusion process for austenites and non-corrosive martensites. Non-magnetic properties are preserved, and the steels become more reliably resistant to wear while retaining their corrosion resistance.

In the automotive industry, high-alloy steels are used primarily in mechanical components. They are valued not only for their amagnetic (non-magnetic) properties, but also for their high wear resistance.

Inlet and outlet valves, for instance, which are subject to high mechanical and thermal stresses, are made from a combination of martensitic steel and austenitic steel – the former is the ideal solution for high, thumping stresses resulting from the cams in the camshaft, while the latter is resistant to the high temperatures and mechanical stresses on the valve plate.

WEAR MECHANISM	REQUIRED PROPERTIES	
Adhesive wear	<ul><li>Low friction coefficient</li><li>Low affinity between the materials (adhesive force, mutual solubility)</li></ul>	
Abrasive wear	<ul> <li>High surface hardness</li> <li>Low friction coefficient</li> <li>Low roughness</li> <li>High fracture toughness</li> </ul>	
Fatigue wear	<ul><li>High surface hardness</li><li>Low friction coefficient</li><li>Low roughness</li><li>High fracture toughness</li></ul>	
Erosion	<ul><li>High surface hardness</li><li>High elasticity</li></ul>	


# **BALITHERM IONIT ST for austenites and martensites**

HEAT TREATMENT	BALITHERM® IONIT ST Austenite	BALITHERM® IONIT ST Martensite
Compound layer thickness	5 – 50 μm	30 – 100 μm
Surface hardness (HV 0.1)	> 1000	> 1000
Max. application temperature	< 550 °C	< 520 °C
Corrosion resistance	Depends on the treatment temperature	

## **Robust protection for toughest demands**



BALITHERM® IONIT ST treated valves withstand high loads in an engine.





High thermal and mechanical loads of the valves during combustion process.

# **BALITHERM IONIT ST for refining of valve steels**

The BALITHERM® IONIT ST process means that Oerlikon Balzers can now offer a nitriding process which significantly improves the wear resistance of the austenite without affecting its non-magnetic properties. As the two materials nitride differently, diffusion depths of 15 µm in the austenite and 30 µm in the martensite can be achieved without any problems, increasing the reliability of their wear resistance. The low process temperature also ensures that no chromium depletion occurs at the edges, helping retain corrosion resistance.

- Non-magnetic properties are preserved
- Corrosion resistance of high-alloy steels is retained
- Scuffing is avoided
- Wear protection for austenitic materials with low core hardness





# Take advantage of the benefits from BALITHERM IONIT ST Get in touch with us today!

# **Balzers Headquarters**

Oerlikon Balzers Coating AG Balzers Technology and Service Centre Iramali 18 LI-9496 Balzers Liechtenstein T +423 388 7500

Oerlikon Metco Surface Technology (Shanghai) Co., Ltd. Changchun Branch Building 3-3, 2177 Changde Road Jingkai District Changchun 13001 T +86 431 81907960

Oerlikon Metco Surface Technology (Shanghai) Co., Ltd. Buildings 1&2, 539 Baian Road Jiading District Shanghai 201814 T +86 21 67087000

### Germany

Oerlikon Metaplas GmbH Theodor-Heuss-Straße 63 38228 Salzgitter T +49 5341 8587-0

Oerlikon Balzers Coating Germany GmbH Am Böttcherberg 30 – 38 51427 Bergisch Gladbach T +49 2204 299-0

Oerlikon Metaplas GmbH Bernd-Beltrame-Straße 5 09399 Niederwürschnitz T +49 37296 9324-0

# Slovakia

Oerlikon Balzers Coating Slovakia s.r.o Industrial Park / Priemyselný park Veľká Ida 770 044 55 Veľká Ida T +421 5532107-10

You can find a full listing of our locations at:

www.oerlikon.com/balzers

