

Glossary

Corporate and financial terms

AGM	Annual General Meeting
CAGR	Compound Annual Growth Rate
CAPEX	Capital expenditure
EBIT	Earnings before interest and tax
EBITDA	Earnings before interest, tax, depreciation and amortization
EMEAR	Europe, Middle East, Africa and Russia
EPS	Earnings per share
HSE	Health, Safety and Environment
KPI	Key Performance Indicator
LTA	Lost time accidents
OOE	Oerlikon operational excellence
R&D	Research and development
ROCE	Return on capital employed
SMI	Swiss Market Index = Switzerland's blue-chip stock market index. It is made up of 20 of the largest and most liquid Swiss Performance Index (SPI) large- and mid-cap stocks.
SMIM	Swiss Market Index Mid = consists of 30 biggest mid-cap Swiss companies which are not included in the SMI
STOXX Europe 600	The Stoxx Europe 600 Index represents large, mid and small capitalization companies across 18 countries of the European region

Surface Solutions Segment

BALIQ™	New generation of wear-resistant coatings with revolutionary properties for a unique spectrum of applications, based on our S3p technology.
ePD™	Embedded PVD for Design Parts
MetcoClad™	Laser Cladding System = a welding process utilizing an infinitely controllable laser beam as its heat source
PPD™ technology	Pulsed-Plasma Diffusion = Oerlikon Balzers' Pulsed-Plasma Diffusion offers a long lasting, cost-effective and environmentally friendly way to harden and protect large manufacturing production tools and dies. Using hydrogen and nitrogen in an electrical discharge, PPD™ technology uses no hazardous chemicals. PPD is an alternative to chrome-plating.
PVD	Physical vapor deposition = a variety of methods used to deposit thin films onto various workpiece surfaces through condensation of the desired thin film material vapourized in vacuum.
S3p™ technology	Scalable Pulsed Power Plasma = a coating technology that combines the advantages of arc and sputtering technologies: high ionisation with virtually no droplets. The result: extremely smooth and dense coatings for a wide variety of applications.

Manmade Fibers Segment

BCF	Bulked Continuous Filament = yarn for carpet production, usually polypropylene, polyester or nylon
HMLS	High-modulus low-shrinkage polyester
Manmade Fibers	Chemical or synthetic fibers
POY	Pre-oriented yarn = the spun yarn is not completely drawn. It is used in textiles, e.g. after being finished using Oerlikon Barmag draw-teturin machines
WINGS	Winding Integrated Godet Solution = brand name of the latest winder technology by Oerlikon Manmade Fibers
WINGS PA HOY	Latest winder technology for high-oriented polyamide yarn

Drive Systems Segment

4SED	4-Speed Electric Drive = four-speed seamless shift electric transmission
OGeco	Hybrid power-shifting automated manual transmission

Vacuum Segment

Cryo pumps	Sophisticated high-vacuum absorption pumps applied to simulate space atmosphere on earth and used in the complex field of research and testing of space components and equipments
OLED	Organic light emitting diodes
PHOENIX L500i	Leak detector
TURBOVAC i/iX	Turbomolecular pumps used for analytics that offer extremely high pumping capacity